

Forks

There are three main fork types available: the pallet fork, the cubing fork and the lumber fork.



Pallet Forks

- handle palletized material and other loads that require transportation and placement



Cubing Forks

- smaller width
- used to load, unload and place cubes of brick and block



Lumber Forks

- wider width
- ideal for separating stacks of lumber

Current Production - Pallet Forks

Available Through JLG Aftermarket Or With New Machine Orders

TYPE		Pallet							
CAPACITY PER FORKAT 24 IN. LOAD CENTER		3,800 lbs.	5475 lbs.	5650 lbs.	6850 lbs.	9,050 lbs.	9,050 lbs.	9,050 lbs.	9,050 lbs.
FORK DIMENSIONS		2" X 4" X 48"	2.25" x 4" x 48"	2.25" x 6" x 72"	2.25" x 5" x 48"	2.25" X 6" X 96"	2.25" X 6" X 72"	2.25" X 6" X 60"	2.25" X 6" X 48"
EYE DIAMETER		2.25 in.	2.25 in.	2.25 in.	2.25 in.	2.75 in.	2.75 in.	2.75 in.	2.75 in.
FORK DROP		24 in.	24 in.	24 in.	24 in.	24 in.	24 in.	24 in.	24 in.
PART NO.		1001099458	2340045	1001092391	2340038	1001196949	1001196950	1001196951	1001196952
Model		SN Break							
JLG	742	ALL	•	•	•				
	943	ALL	•	•	•				
	1043	ALL	•	•	•				
	1055	ALL	•	•	•				
	1255	ALL		•	•				
	1644	ALL				•	•	•	•
	1732	ALL				•	•	•	•
	G5-18A	ALL	•						
SKYTRAK™	6036	0160069720 - Present, incl 0160065792, 0160065798, 0160065824, 0160069383 & 0160069411	•	•	•				
	6042	0160069720 - Present, incl 0160065792, 0160065798, 0160065824, 0160069383 & 0160069411	•	•	•				
	8042	0160069722 - Present, incl 0160065791, 0160065796, 0160065825, 0160065826, 0160069336, 0160069359 & 0160069441	•	•	•				
	10042	0160069722 - Present, incl 0160065791, 0160065796, 0160065825, 0160065826, 0160069336, 0160069359 & 0160069441	•	•	•				
	10054	0160069722 - Present, incl 0160065791, 0160065796, 0160065825, 0160065826, 0160069336, 0160069359 & 0160069441	•	•	•				

NOTES:

- Use only JLG approved attachments with proper material handler model/attachment load capacity charts displayed in the operator's cab.
 - Forks rated less than the attachment and/or machine capacity decrease the capacity of the attachment and machine to that of the forks.
 - Forks rated more than the attachment and/or machine capacity do not increase the attachment or machine capacity.
 - Never use your attachment as a work platform or personnel carrier.
- Can't find the attachment you are looking for? Contact your JLG Aftermarket Parts representative at 1-877-JLG-LIFT or visit www.jlg.com.

CURRENT & NON-CURRENT FORKS | JLG/SKYTRAK

Current Production - Cubing and Lumbar Forks

Available Through JLG Aftermarket Or With New Machine Orders

TYPE		Cubing	Lumber			
CAPACITY PER FORK AT 24 IN. LOAD CENTER		1940 lbs.	3650 lbs.	5400 lbs.	6850 lbs.	8150 lbs.
FORK DIMENSIONS		2"x2"x48"	1.5"x6"x60"	1.75"x7"x60"	2"x7"x60"	2.25"x6"x60"
EYE DIAMETER		2.25 in.	2.25 in.	2.25 in.	2.25 in.	2.25 in.
FORK DROP		24 in.	24 in.	24 in.	24 in.	24 in.
PART NO.		2340037	1001099457	2340046	1001097110	2340039
Model	SN Break					
JLG	742	ALL	•	•	•	•
	943	ALL	•	•	•	•
	1043	ALL	•	•	•	•
	1055	ALL	•	•	•	•
	1255	ALL	•	•	•	•
	1644	ALL				
	1732	ALL				
	G5-18A	ALL	•	•		
SKYTRAK™	6036	0160069720 - Present, incl 0160065792, 0160065798, 0160065824, 0160069383 & 0160069411	•	•	•	•
	6042	0160069720 - Present, incl 0160065792, 0160065798, 0160065824, 0160069383 & 0160069411	•	•	•	•
	8042	0160069722 - Present, incl 0160065791, 0160065796, 0160065825, 0160065826, 0160069336, 0160069359 & 0160069441	•	•	•	•
	10042	0160069722 - Present, incl 0160065791, 0160065796, 0160065825, 0160065826, 0160069336, 0160069359 & 0160069441	•	•	•	•
	10054	0160069722 - Present, incl 0160065791, 0160065796, 0160065825, 0160065826, 0160069336, 0160069359 & 0160069441	•	•	•	•

Non-Current Production - Pallet Forks, JLG

Available Through JLG Aftermarket Parts

TYPE		Pallet						
CAPACITY PER FORK AT 24 IN. LOAD CENTER		3800 lbs.	4409 lbs. (rated at 20" load center)	4409 lbs. (rated at 20" load center)	5475 lbs.	5475 lbs.	5650 lbs.	5650 lbs.
FORK DIMENSIONS		2"x4"x48"	1.75"x5"x48"	2"x4"x48"	2.25"x4"x48"	2.25"x4"x48"	2"x6"x60"	2.25"x6"x72"
EYE DIAMETER		2.25 in.	2.375 in.	2.375 in.	2.25 in.	2.25 in.	2.25 in.	2.25 in.
FORK DROP		24 in.	28 in.	28 in.	20 in.	24 in.	25.5 in.	24 in.
PART NO.		1001099458	2340029	2340030	91513206	2340045	91403580	1001092391
Model	SN Break							
JLG	642	ALL				•		•
	619A	ALL	•					
	723A	ALL	•					•
	G5-19A	ALL		•	•			
	G6-23A	ALL		•	•			
	G6-42A	Prior To 0160037722				•	•	•
	G6-42A	0160037722 - Present					•	•
	G9-43A	Prior To 0160037671	•			•	•	•
	G9-43A	0160037671 - Present					•	•
	G10-43A	ALL					•	•
	G10-55A	Prior To 0160037689				•	•	•
	G10-55A	0160037689 - Present					•	•
	G12-55A	Prior To 0160037689				•	•	•
	G12-55A	0160037689 - Present					•	•
	TF6-42	ALL				•	•	•

NOTES:

- Use only JLG approved attachments with proper material handler model/attachment load capacity charts displayed in the operator's cab.
- Forks rated less than the attachment and/or machine capacity decrease the capacity of the attachment and machine to that of the forks.
- Forks rated more than the attachment and/or machine capacity do not increase the attachment or machine capacity.
- Never use your attachment as a work platform or personnel carrier.

Can't find the attachment you are looking for? Contact your JLG Aftermarket Parts representative at 1-877-JLG-LIFT or visit www.jlg.com.

Pallet options continue on next page

Non-Current Production - Pallet Forks, JLG

Available Through JLG Aftermarket Parts

TYPE		Pallet				Pallet (Sold as Set)			Pallet (Fork Positioning Carriage Only)
CAPACITY PER FORK AT 24 IN. LOAD CENTER		6850 lbs.	6850 lbs.	7500 lbs.	8150 lbs.	4409 lbs. (rated at 20" load center)	4409 lbs. (rated at 20" load center)	4409 lbs.	5000 lbs.
FORK DIMENSIONS		2.25"x5"x48"	2.25"x5"x48"	2.36"x6"x48"	2.25"x6"x60"	2"x4"x48"	2"x5"x48"	2.25"x4"x48"	2.25"x4"x48"
EYE DIAMETER		2.25 in.	2.25 in.	2.31 in.	2.25 in.	2.375 in.	2.375 in.	2.375 in.	2 in.
FORK DROP		20 in.	24 in.	24 in.	20 in.	21.5 in.	21.5 in.	21.5 in.	24 in.
PART NO.		91563141	2340038	1001193801	91563142	2340041	1001117945	1001107586	7301408
Model	SN Break								
JLG	642	ALL	•						
	723A	ALL	•						
	G5-19A	ALL				•	•	•	
	G6-23A	ALL				•	•	•	
	G6-42A	Prior To 0160037722	•	•		•			
	G6-42A	0160037722 - Present		•					•
	G9-43A	Prior To 0160037671	•	•		•			
	G9-43A	0160037671 - Present		•					•
	G10-43A	ALL		•					•
	G10-55A	Prior To 0160037689	•	•		•			
	G10-55A	0160037689 - Present		•					•
	G12-55A	Prior To 0160037689	•	•		•			
	G12-55A	0160037689 - Present		•					•
	G15-44A	ALL			•				
	TF6-42	ALL	•	•		•			

Non-Current Production - Cubing and Drywall Forks, JLG

Available Through JLG Aftermarket Parts

TYPE		Cubing		Cubing (Sold as Set)	Drywall	
CAPACITY PER FORK AT 24 IN. LOAD CENTER		1940 lbs.		1940 lbs.	2500 lbs.	
FORK DIMENSIONS		2"x2"x48"		2"x2"x48"	1.75"x4"x48"	
EYE DIAMETER		2.25 in.		2.375"	2.25 in.	
FORK DROP		20 in.		24 in.	21.5 in.	
PART NO.		91403359		2340037	10010979225	
	Model	SN Break				
JLG	642	ALL		•		
	619A	ALL		•		
	723A	ALL		•		
	G5-19A	ALL			•	
	G6-23A	ALL			•	
	G6-42A	Prior To 0160037722	•	•		•
	G6-42A	0160037722 - Present		•		
	G9-43A	Prior To 0160037671	•	•		•
	G9-43A	0160037671 - Present		•		
	G10-43A	ALL		•		
	G10-55A	Prior To 0160037689	•	•		•
	G10-55A	0160037689 - Present		•		
	G12-55A	Prior To 0160037689	•	•		•
	G12-55A	0160037689 - Present		•		
	TF6-42	ALL	•	•		•

NOTES:

- Use only JLG approved attachments with proper material handler model/attachment load capacity charts displayed in the operator's cab.
 - Forks rated less than the attachment and/or machine capacity decrease the capacity of the attachment and machine to that of the forks.
 - Forks rated more than the attachment and/or machine capacity do not increase the attachment or machine capacity.
 - Never use your attachment as a work platform or personnel carrier.
- Can't find the attachment you are looking for? Contact your JLG Aftermarket Parts representative at 1-877-JLG-LIFT or visit www.jlg.com.

Non-Current Production - Lumber Forks, JLG

Available Through JLG Aftermarket Parts

TYPE		Lumber						Dual Taper
CAPACITY PER FORK AT 24 IN. LOAD CENTER		3050 lbs.	3650 lbs.	5400 lbs.	6850 lbs.	8150 lbs.	8150 lbs.	7500 lbs.
FORK DIMENSIONS		1.75"x4"x48"	1.5"x6"x60"	1.75"x7"x60"	2"x7"x60"	2.25"x6"x60"	2.25"x6"x72"	2.36"x6"x72"
EYE DIAMETER		2.25 in.	2.2 in.	2.25 in.	2.25 in.	2.25 in.	2.25 in.	2.31 in.
FORK DROP		25.5 in.	24 in.	24 in.	24 in.	24 in.	20 in.	24 in.
PART NO.		91403364	1001099457	2340046	1001097110	2340039	91563143	1001193802
Model	SN Break							
JLG	642	ALL	▪		▪	▪		
	619A	ALL	▪					
	723A	ALL	▪					
	G6-42A	Prior To 0160037722	▪	▪		▪	▪	
	G6-42A	0160037722 - Present		▪		▪		
	G9-43A	Prior To 0160037671	▪	▪		▪	▪	
	G9-43A	0160037671 - Present		▪		▪		
	G10-43A	ALL		▪		▪		
	G10-55A	Prior To 0160037689	▪	▪		▪	▪	
	G10-55A	0160037689 - Present		▪		▪		
	G12-55A	Prior To 0160037689	▪	▪		▪	▪	
	G12-55A	0160037689 - Present		▪		▪		
	G15-44A	ALL						▪
	TF6-42	ALL	▪		▪		▪	



NOTES:

- Use only JLG approved attachments with proper material handler model/attachment load capacity charts displayed in the operator's cab.
 - Forks rated less than the attachment and/or machine capacity decrease the capacity of the attachment and machine to that of the forks.
 - Forks rated more than the attachment and/or machine capacity do not increase the attachment or machine capacity.
 - Never use your attachment as a work platform or personnel carrier.
- Can't find the attachment you are looking for? Contact your JLG Aftermarket Parts representative at 1-877-JLG-LIFT or visit www.jlg.com.

Non-Current Production - Pallet Forks, Gradall

Available Through JLG Aftermarket Parts

TYPE		Pallet								
CAPACITY PER FORK AT 24 IN. LOAD CENTER		3750 lbs. (rated at 48" load center)	4000 lbs.	4500 lbs.	5000 lbs.	5000 lbs.	5000 lbs.	5475 lbs.	5475 lbs.	
FORK DIMENSIONS		2"x6"x96"	2"x4"x48"	1.75"x6"x48"	2"x6"x48"	2"x6"x60"	2"x6"x72"	2.25"x4"x48"	2.25"x4"x48"	
EYE DIAMETER		2 in.	2 in.	2 in.	2 in.	2 in.	2 in.	2 in.	2.25 in.	
FORK DROP		20 in.	20 in.	20 in.	20 in.	20 in.	20 in.	20.5 in.	20 in.	
PART NO.		H0453002	90453002	90601819	90553005	90601015	90553018	90453048	91513206	
Model	SN Break									
GRADALL	522D/524D	ALL	
	534C-9	ALL	
	534C-10	ALL	
	534D-6	ALL	
	534D-9	Prior To 0160037689
		0160037689 - Present								
	534D-10	Prior To 0160037689
		0160037689 - Present								
	544C	ALL	
	544D	Prior To 0160037689
		0160037689 - Present								
	G6-42P	Prior To 0160037689								.
0160037689 - Present										

Non-Current Production - Pallet Forks, Gradall

Available Through JLG Aftermarket Parts

TYPE		Pallet						Pallet (Swing Mast Carriage Only)		
CAPACITY PER FORK AT 24 IN. LOAD CENTER		5475 lbs.	5650 lbs.	5650 lbs.	6850 lbs.	6850 lbs.	8150 lbs.	2500 lbs.	5650 lbs.	
FORK DIMENSIONS		2.25"x4"x48"	2"x6"x60"	2.25"x6"x72"	2.25"x5"x48"	2.25"x5"x48"	2.25"x6"x60"	1.75"x4"x48"	2"x6"x60"	
EYE DIAMETER		2.25 in.	2.25 in.	2.25 in.	2.25 in.	2.25 in.	2.25 in.	2 in.	2 in.	
FORK DROP		24 in.	25.5 in.	24 in.	20 in.	24 in.	20 in.	25.5 in.	25.5 in.	
PART NO.		2340045	91403580	1001092391	91563141	2340038	91563142	90553008	90453045	
Model	SN Break									
GRADALL	522D/524D	ALL								
	534C-9	ALL						.	.	
	534C-10	ALL						.	.	
	534D-6	ALL						.	.	
	534D-9	Prior To 0160037689
		0160037689 - Present
	534D-10	Prior To 0160037689
		0160037689 - Present
	544C	ALL						.	.	
	544D	Prior To 0160037689
		0160037689 - Present
	G6-42P	Prior To 0160037689
0160037689 - Present		

NOTES:

- Use only JLG approved attachments with proper material handler model/attachment load capacity charts displayed in the operator's cab.
 - Forks rated less than the attachment and/or machine capacity decrease the capacity of the attachment and machine to that of the forks.
 - Forks rated more than the attachment and/or machine capacity do not increase the attachment or machine capacity.
 - Never use your attachment as a work platform or personnel carrier.
- Can't find the attachment you are looking for? Contact your JLG Aftermarket Parts representative at 1-877-JLG-LIFT or visit www.jlg.com.

NON-CURRENT FORKS | GRADALL

Non-Current Production - Cubing and Drywall Forks, Gradall

Available Through JLG Aftermarket Parts

TYPE		Cubing			Drywall		
CAPACITY PER FORK AT 24 IN. LOAD CENTER		1500 lbs.	1940 lbs.	1940 lbs.	2500 lbs.	2500 lbs.	
FORK DIMENSIONS		2"x2"x48"	2"x2"x48"	2"x2"x48"	1.75"x4"x48"	1.75"x4"x48"	
EYE DIAMETER		2 in.	2.25 in.	2.25 in.	2 in.	2.25 in.	
FORK DROP		20 in.	20 in.	24 in.	29 in.	29 in.	
PART NO.		90600390	91403359	2340037	90453013	91403366	
Model	SN Break						
GRADALL	522D/524D	ALL	•		•		
	534C-9	ALL	•		•		
	534C-10	ALL	•		•		
	534D-6	ALL	•		•		
	534D-9	Prior To 0160037689	•		•	•	
		0160037689 - Present			•		
	534D-10	Prior To 0160037689	•		•	•	
		0160037689 - Present			•		
	544C	ALL	•		•		
	544D	Prior To 0160037689	•		•	•	
		0160037689 - Present			•		
	G6-42P	Prior To 0160037689		•	•		•
		0160037689 - Present			•		

Non-Current Production - Lumber Forks, Gradall

Available Through JLG Aftermarket Parts

TYPE		Lumber						
CAPACITY PER FORK AT 24 IN. LOAD CENTER		3050 lbs.	5000 lbs.	5400 lbs.	5650 lbs.	8150 lbs.	8150 lbs.	
FORK DIMENSIONS		1.75"x4"x48"	2"x6"x72"	1.75"x7"x60"	2"x6"x60"	2.25"x6"x60"	2.25"x6"x72"	
EYE DIAMETER		2.25 in.	2 in.	2.25 in.	2 in.	2.25 in.	2.25 in.	
FORK DROP		25.5 in.	20 in.	24 in.	20 in.	24 in.	20 in.	
PART NO.		91403364	91123132	2340046	91163269	2340039	91563143	
Model	SN Break							
GRADALL	522D/524D	ALL	•		•			
	534C-9	ALL	•		•			
	534C-10	ALL	•		•			
	534D-6	ALL	•		•			
	534D-9	Prior To 0160037689		•	•	•	•	
		0160037689 - Present			•		•	
	534D-10	Prior To 0160037689		•	•	•	•	
		0160037689 - Present			•		•	
	544C	ALL	•		•			
	544D	Prior To 0160037689	•		•	•	•	
		0160037689 - Present			•		•	
	G6-42P	Prior To 0160037689	•		•		•	•
		0160037689 - Present			•		•	

NOTES:

- Use only JLG approved attachments with proper material handler model/attachment load capacity charts displayed in the operator's cab.
 - Forks rated less than the attachment and/or machine capacity decrease the capacity of the attachment and machine to that of the forks.
 - Forks rated more than the attachment and/or machine capacity do not increase the attachment or machine capacity.
 - Never use your attachment as a work platform or personnel carrier.
- Can't find the attachment you are looking for? Contact your JLG Aftermarket Parts representative at 1-877-JLG-LIFT or visit www.jlg.com.

Non-Current Production - Pallet Forks, SkyTrak
Available Through JLG Aftermarket Parts

TYPE		Pallet							
CAPACITY PER FORK AT 24 IN. LOAD CENTER		3000 lbs.	4000 lbs.	5000 lbs.	5060 lbs.	5475 lbs.	5600 lbs.	6850 lbs.	
FORK DIMENSIONS		1.75"x4"x48"	2"x4"x48"	2"x4"x48"	2"x5"x72"	2.25"x4"x48"	2.25"x6"x72"	2.25"x5"x48"	
EYE DIAMETER		2 in.	2 in.	2 in.	2 in.	2.25 in.	2.25 in.	2.25 in.	
FORK DROP		22 in.	24 in.	24 in.	24 in.	24 in.	24 in.	24 in.	
PART NO.		7048233	7097523	7301408	2340042	2340045	1001092391	2340038	
Model	SN Break								
SKYTRAK	4266	ALL	
	4270	ALL	
	4290	ALL	
	6036	Prior To 0160031200
		0160031200 - 016009719, excl 0160065792, 0160065798, 0160065824, 0160069383 & 0160069411
	6042	Prior To 0160031200
		0160031200 - 016009719, excl 0160065792, 0160065798, 0160065824, 0160069383 & 0160069411
	8042	Prior To 0160031235
		0160031235 - 0160069721, excl 0160065791, 0160065796, 0160065825, 0160065826, 0160069336, 0160069359 & 0160069441
	10042	Prior To 0160031425
		0160031425 - 0160069721, excl 0160065791, 0160065796, 0160065825, 0160065826, 0160069336, 0160069359 & 0160069441
	10054	Prior To 0160031255
0160031255 - 0160069721, excl 0160065791, 0160065796, 0160065825, 0160065826, 0160069336, 0160069359 & 0160069441		

Non-Current Production - Cubing, Drywall and Lumber Forks, SkyTrak
Available Through JLG Aftermarket Parts

TYPE		Cubing		Drywall	Lumber					
CAPACITY PER FORK AT 24 IN. LOAD CENTER		1940 lbs.	2000 lbs.	5000 lbs.	3000 lbs.	5400 lbs.	5650 lbs.	6000 lbs.	8150 lbs.	
FORK DIMENSIONS		2"x2"x48"	2"x2"x48"	1.75"x7"x48"	1.75"x5"x60"	1.75"x7"x60"	2"x6"x60"	1.75"x7"x60"	2.25"x6"x60"	
EYE DIAMETER		2.25 in.	2 in.	2 in.	2 in.	2.25 in.	2 in.	2 in.	2.25 in.	
FORK DROP		24 in.	22 in.	24 in.	24 in.	24 in.	24 in.	24 in.	24 in.	
PART NO.		2340037	7139747	7130453	7092793	2340046	2340036	7139746	2340039	
Model	SN Break									
SKYTRAK	4266	ALL	
	4270	ALL	
	4290	ALL	
	6036	Prior To 0160031200
		0160031200 - 016009719, excl 0160065792, 0160065798, 0160065824, 0160069383 & 0160069411
	6042	Prior To 0160031200
		0160031200 - 016009719, excl 0160065792, 0160065798, 0160065824, 0160069383 & 0160069411
	8042	Prior To 0160031235
		0160031235 - 0160069721, excl 0160065791, 0160065796, 0160065825, 0160065826, 0160069336, 0160069359 & 0160069441
	10042	Prior To 0160031425
		0160031425 - 0160069721, excl 0160065791, 0160065796, 0160065825, 0160065826, 0160069336, 0160069359 & 0160069441
	10054	Prior To 0160031255
0160031255 - 0160069721, excl 0160065791, 0160065796, 0160065825, 0160065826, 0160069336, 0160069359 & 0160069441		

NOTES:

- Use only JLG approved attachments with proper material handler model/attachment load capacity charts displayed in the operator's cab.
 - Forks rated less than the attachment and/or machine capacity decrease the capacity of the attachment and machine to that of the forks.
 - Forks rated more than the attachment and/or machine capacity do not increase the attachment or machine capacity.
 - Never use your attachment as a work platform or personnel carrier.
- Can't find the attachment you are looking for? Contact your JLG Aftermarket Parts representative at 1-877-JLG-LIFT or visit www.jlg.com.

NON-CURRENT FORKS | LULL

Non-Current Production - Pallet Forks, Lull

Available Through JLG Aftermarket Parts

TYPE		Pallet								
CAPACITY PER FORK AT 24 IN. LOAD CENTER		4000 lbs.	4000 lbs.	4000 lbs.	5000 lbs.	5000 lbs.	5000 lbs.	5000 lbs.	5000 lbs.	
FORK DIMENSIONS		2"x4"x42"	2"x4"x48"	2"x4"x60"	2"x4"x48"	2"x5"x42"	2"x5"x48"	2"x5"x60"	2.25"x4"x42"	
EYE DIAMETER		1.875 in.	1.875 in.	1.875 in.	2 in.	2 in.	2 in.	2 in.	2 in.	
FORK DROP		25 in.	27 in.	25 in.	24 in.	25 in.	27 in.	27 in.	25 in.	
PART NO.		10238026	1001099850	10238117	7301408	10238568	1001099846	1001099848	10239893	
Model	SN Break									
LULL	644B-37	ALL	•	•	•					
	644B-42	ALL	•	•	•					
	644D-34	ALL	•	•	•					
	644E-42	Prior To 0160037794				•				
		0160037794 - Present				•				
	844C-42	ALL	•	•	•					
	944E-42	Prior To 0160037794				•				
	1044C-42	ALL				•	•	•	•	
	1044C-54	ALL				•	•	•	•	
	1044C-54 SII	Prior To 0160037893		•			•	•	•	
		0160037893 - Present				•				
	6K-37	ALL	•	•	•					
	6K-42	ALL	•	•	•					
8K-42	ALL	•	•	•						
10K-42/10K-54	ALL					•	•	•	•	

Non-Current Production - Pallet Forks, Lull

Available Through JLG Aftermarket Parts

Pallet options continue below

TYPE		Pallet				Pallet (Swing Carriage Only)		Pallet (Fork Positioning Carriage Only)			
CAPACITY PER FORK AT 24 IN. LOAD CENTER		5000 lbs.	5475 lbs.	5600 lbs.	6850 lbs.	5000 lbs.	5060 lbs.	4000 lbs.	4000 lbs.	5000 lbs.	
FORK DIMENSIONS		2.25"x4"x48"	2.25"x4"x48"	2.25"x6"x72"	2.25"x5"x48"	2"x5"x60"	2"x5"x48"	2"x4"x42"	2"x4"x48"	2"x5"x42"	
EYE DIAMETER		2 in.	2.25 in.	2.25 in.	2.25 in.	2.25 in.	2.25 in.	2.75 in.	2.75 in.	2.75 in.	
FORK DROP		27 in.	24 in.	24 in.	24 in.	22 in.	22 in.	25 in.	25 in.	25 in.	
PART NO.		1001099847	2340045	1001092391	2340038	10239970	2340048	10338502 (LH) 10338503 (RH)	10339345 (LH) 10339346 (RH)	10365687 (LH) 10365686 (RH)	
Model	SN Break										
LULL	644B-37	ALL						•	•		
	644B-42	ALL						•	•		
	644D-34	ALL									
	644E-42	Prior To 0160037794		•		•					
		0160037794 - Present		•	•	•					
	844C-42	ALL						•	•		
	944E-42	Prior To 0160037794		•		•					
	1044C-42	ALL	•							•	
	1044C-54	ALL	•							•	
	1044C-54 SII	Prior To 0160037893	•				•	•			•
		0160037893 - Present		•	•	•					
	6K-37	ALL						•	•		
	6K-42	ALL						•	•		
8K-42	ALL						•	•			
10K-42/10K-54	ALL	•									

NOTES:

- Use only JLG approved attachments with proper material handler model/attachment load capacity charts displayed in the operator's cab.
 - Forks rated less than the attachment and/or machine capacity decrease the capacity of the attachment and machine to that of the forks.
 - Forks rated more than the attachment and/or machine capacity do not increase the attachment or machine capacity.
 - Never use your attachment as a work platform or personnel carrier.
- Can't find the attachment you are looking for? Contact your JLG Aftermarket Parts representative at 1-877-JLG-LIFT or visit www.jlg.com.

Non-Current Production - Cubing and Lumber Forks, Lull

Available Through JLG Aftermarket Parts

TYPE		Cubing				Lumber			
CAPACITY PER FORK AT 24 IN. LOAD CENTER		1940 lbs.	2000 lbs.	2000 lbs.	2000 lbs.	4000 lbs.	4000 lbs.	5000 lbs.	
FORK DIMENSIONS		2"x2"x48"	2"x2"x48"	2"x2"x48"	2"x2"x48"	1.75"x6"x48"	1.75"x6"x60"	1.75"x7"x48"	
EYE DIAMETER		2.25 in.	2 in.	2 in.	2 in.	1.875 in.	1.875 in.	2 in.	
FORK DROP		24 in.	22 in.	25 in.	27 in.	25 in.	25 in.	25 in.	
PART NO.		2340037	7139747	10238118	1001099845	10217103	10223610	10239094	
Model	SN Break								
LULL	644B-37	ALL		•		•	•		
	644B-42	ALL		•		•	•		
	644D-34	ALL		•		•	•		
	644E-42	Prior To 0160037794	•	•					
		0160037794 - Present	•						
	844C-42	ALL		•		•	•		
	944E-42	Prior To 0160037794	•	•					
	1044C-42	ALL		•	•			•	
	1044C-54	ALL		•	•			•	
	1044C-54 SII	Prior To 0160037893		•	•				
		0160037893 - Present	•						
	6K-37	ALL		•		•	•		
	6K-42	ALL		•		•	•		
8K-42	ALL		•		•	•			
10K-42/10K-54	ALL		•	•			•		

Lumber options continue below

Non-Current Production - Lumber Forks, Lull

Available Through JLG Aftermarket Parts

TYPE		Lumber						Lumber (Swing Carriage Only)			
CAPACITY PER FORK AT 24 IN. LOAD CENTER		5000 lbs.	5000 lbs.	5000 lbs.	5400 lbs.	5650 lbs.	6000 lbs.	8150 lbs.	4000 lbs.	5000 lbs.	
FORK DIMENSIONS		1.75"x7"x60"	2"x6"x48"	2"x6"x60"	1.75"x7"x60"	2"x6"x60"	1.75"x7"x60"	2.25"x6"x60"	1.75"x6"x48"	1.75"x7"x60"	
EYE DIAMETER		2 in.	2 in.	2 in.	2.25 in.	2 in.	2 in.	2.25 in.	2.25 in.	2.25 in.	
FORK DROP		27 in.	29.5 in.	29.5 in.	24 in.	24 in.	24 in.	24 in.	22 in.	22 in.	
PART NO.		1001099849	10238181	10238182	2340046	2340036	7139746	2340039	10239954	10239969	
Model	SN Break										
LULL	644B-37	ALL									
	644B-42	ALL									
	644D-34	ALL									
	644E-42	Prior To 0160037794				•	•	•			
		0160037794 - Present				•		•			
	844C-42	ALL									
	944E-42	Prior To 0160037794				•	•	•			
	1044C-42	ALL	•	•	•						
	1044C-54	ALL	•	•	•						
	1044C-54 SII	Prior To 0160037893	•						•	•	
		0160037893 - Present				•		•			
	6K-37	ALL									
	6K-42	ALL									
8K-42	ALL										
10K-42/10K-54	ALL	•	•	•							

NOTES:

- Use only JLG approved attachments with proper material handler model/attachment load capacity charts displayed in the operator's cab.
 - Forks rated less than the attachment and/or machine capacity decrease the capacity of the attachment and machine to that of the forks.
 - Forks rated more than the attachment and/or machine capacity do not increase the attachment or machine capacity.
 - Never use your attachment as a work platform or personnel carrier.
- Can't find the attachment you are looking for? Contact your JLG Aftermarket Parts representative at 1-877-JLG-LIFT or visit www.jlg.com.